

MSZ-HJ25VA and HJ35VA - Inverter Heat Pump - Classic Wall Mounted System



Brand: Mitsubishi
Weight: 0.00kg
Dimensions: 0.00cm x 0.00cm x 0.00cm

Short Description

Classic wall mounted reverse cycle heating and cooling air conditioning units in the 2.5 - 3.5 KW capacity range.

Description

R410A Wall Mounted Air Conditioning Models

Mitsubishi Electric's range of high specification wall mounted air conditioning units have, flat panel wall mounted reverse cycle heating and cooling models make use of inverter technology, whilst providing extremely good value for money.

These units have extremely quiet sound levels, whilst also delivering economical air conditioning, with improved SCOP/SEER figures.

Specifications for HJ35VA

INDOOR

Heating Capacity (kW) (nominal)	3.6 (0.9 - 4.8)
Cooling Capacity (kW) (nominal)	3.15 (1 - 3.7)
Heating Capacity (kW) (UK)	2.99 (0.74 - 3.98)
Cooling Capacity (kW) (UK)	3.12 (0.99 - 3.67)

SHF (nominal and UK)	0.87
COP / EER (nominal)	3.62 / 3.03
SCOP / SEER	3.8 / 5.1
Energy Label (nominal)	A / B
Airflow (m ³ /min) (Heating) - Lo-Mi-Hi-SupHi	3.4 - 5.5 - 7.5 - ?
Airflow (m ³ /min) (Cooling) - Lo-Mi-Hi-SupHi	3.8 - 5.7 - 7.8 - ?
Pipe Size Gas (mm [in])	9.52 (3/8)
Pipe Size Liquid (mm ([in]))	6.35 (1/4)
Sound Pressure Level (dBA) Heating - Lo-Mi-Hi-SupHi	23 - 30 - 37 - 44
Sound Pressure Level (dBA) Cooling - Lo-Mi-Hi-SupHi	22 - 31 - 37 - ?
Sound Power Level (dBA) Cooling	60
Dimensions (mm) Width x Depth x Height	799 x 232 x 290
Weight (kg)	9
Electrical Supply	220-240V, 50HZ
Phase	SINGLE
Fuse Rating (BS88) - HRC (A)	10
Interconnecting Cable No. Cores	4
OUTDOOR	
Sound Pressure Level (dBA) Heating / Cooling	50 / 50

Sound Power Level (dBA) Cooling	64
Weight (kg)	25
Dimensions (mm) Width x Depth x Height	699 x 249 x 530
Electrical Supply	FED BY INDOOR UNIT
Phase	SINGLE
System Power Input (kW) - Heating / Cooling (nominal)	0.995 / 1.04
System Power Input (kW) - Heating / Cooling (UK)	0.9 / 0.83
Starting Current (A)	4.9
System Running Current (A) [MAX] - Heating / Cooling	4.8 / 4.9 [6.5]
Fuse Rating (BS88) - HRC (A)	10
Mains Cable No. Cores	3
Max Pipe Length (m)	20
Max Height Difference (m)	12
Charge R410A (kg) - (pre charged length)	0.72 (7)

Specifications for HJ25VA

INDOOR

Heating Capacity (kW) (nominal)	3.15 (0.9 - 4.4)
Cooling Capacity (kW) (nominal)	2.5 (0.9 - 3)
Heating Capacity (kW) (UK)	2.61 (0.74 - 3.65)
Cooling Capacity (kW) (UK)	2.48 (0.89 - 2.97)

SHF (nominal and UK)	0.89
COP / EER (nominal)	3.62 / 3.42
SCOP / SEER	3.8 / 5.1
Energy Label (nominal)	A / A
Airflow (m ³ /min) (Heating) - Lo-Mi-Hi-SupHi	3.4 - 5.5 - 7.5 - ?
Airflow (m ³ /min) (Cooling) - Lo-Mi-Hi-SupHi	3.8 - 5.5 - 7.3 - ?
Pipe Size Gas (mm [in])	9.52 (3/8)
Pipe Size Liquid (mm ([in]))	6.35 (1/4)
Sound Pressure Level (dBA) Heating - Lo-Mi-Hi-SupHi	23 - 30 - 37 - 43
Sound Pressure Level (dBA) Cooling - Lo-Mi-Hi-SupHi	22 - 30 - 37 - ?
Sound Power Level (dBA) Cooling	57
Dimensions (mm) Width x Depth x Height	799 x 232 x 290
Weight (kg)	9
Electrical Supply	220-240V, 50HZ
Phase	SINGLE
Fuse Rating (BS88) - HRC (A)	10
Interconnecting Cable No. Cores	4
OUTDOOR	
Sound Pressure Level (dBA) Heating / Cooling	50 / 50

Sound Power Level (dBA) Cooling	63
Weight (kg)	24
Dimensions (mm) Width x Depth x Height	699 x 249 x 530
Electrical Supply	FED BY INDOOR UNIT
Phase	SINGLE
System Power Input (kW) - Heating / Cooling (nominal)	0.87 / 0.73
System Power Input (kW) - Heating / Cooling (UK)	0.79 / 0.58
Starting Current (A)	4.2
System Running Current (A) [MAX] - Heating / Cooling	4.2 / 3.7 [5.8]
Fuse Rating (BS88) - HRC (A)	10
Mains Cable No. Cores	3
Max Pipe Length (m)	20
Max Height Difference (m)	12
Charge R410A (kg) - (pre charged length)	0.7 (7)

Product Gallery

